

## AMD® LX800 Process Thin Client



### Features

- Intelligent, cost-effective Client.
- Low-power consumption
- Low temperature operation
- Unique and niche box
- Linux Based Terminal to support Terminal Service on Windows Server

### Specifications

- AMD LX800 processor on board.
- 128MB DDR Memory on board (expandable up to 512MB)
- Small Form Factor – case size 1.26"(W) x 6.58"(H) x 5.1"(D)
- Fan-less, Low Temperature design
- Low-power consumption – 5W typical, 1W standby
- No moving parts in the device
- Display resolutions: 1024 x 768, 1280 x 1024, 1600 x 1200 x 32bpp, 100Hz, 1920 x 1440 x 32bpp, 85Hz.
- 4 x USB 2.0 ports
- 1 x 10/100Mbps High bandwidth Ethernet
- Diskless with non-volatile storage via Flash Disk (Expandable to 6GB)
- Additional Audio peripheral connectivity to earphone and microphone
- Support multiple protocols (ICA, RDP, PXE, TCP/IP)
- Support Local Application (Web browser)
- Support Linux based operating systems

### Application Markets

The Model CS-800 thin client is designed to be used in the following environment and applications:

- Application Terminals for an Enterprise
- Multiple Clients for POS, KIOSK, Advertising Demo Window.
- Terminal Clients for a school
- Information Appliance

### Mechanical & Environmental

Power supply : +12V DC external power adapter (11V to 13V)

- Power requirement : 12V / 1A
- Power Consumption : 5W
- Operating temperature : 0 ~ 60°C

Note : All Specifications are subject to change without notice.