

RS-2917K : 17" KIOSK OEM/ODM



SPECIFICATIONS

Processor	Onboard VIA V4 Eden 1.0GHz or C7 1.5GHz processor
Chipset	VIA CN700 / VT8237R
Memory	2x DDR2 DIMM, Max. 2GB, 400/533MHz
Storage	2.5" IDE or 3.5" SATA hard drive (Max. 2TB) Compact Flash slot
Video	17" (1280 x 1024) SXGA TFT-LCD with CCFL backlight, 16.7M colors Integrated VIA® UniChrome Pro Graphics (share memory 16~64MB) VGA port (support 800x600 ~ 1600x1200 resolution) Support for simultaneous display on LCD and external monitor
Audio	VIA VT1618 6-channel AC'97 Rev 2.3 CODEC Two integrated stereo speakers

	Line out / line in / microphone ports
Interface ports	PS/2 Keyboard PS/2 Mouse RJ45 LAN 4x USB 2.0 4x Serial : 3xRS232, 1x RS232/422/485 VGA Line out / line in / microphone DC-in CF/Micro Drive SD/MS/SM/MMC USB 2.0
Touch Screen	17", 5 wire resistive touch screen
USB Port	7x USB 2.0 ports
Card Reader	CF/Micro Drive/MS/MS Pro (Due) /SM/SD/MMC
Expansion Slots	1x Mini PCI slot
Communications	Realtek 8110SC Gigabit LAN, Wake-on-LAN ready
Watch Dog	Can be set by 500ms, 1, 2, 4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer
Power Lost Recovery	System will auto power on when AC connected. Don't need to press power button.
Packing	Wooden case + foam
Enclosure	2.0mm SPCC
Power Adapter	Input : AC / 100~240V (50/60Hz) 2.5A Output : DC/12V, 5A 60W
Optional	

Color	We can paint your own color
OS	Windows 7 / XP Pro Embedded
Specifications are subject to change without notice.	