

17" VIA® Eden / C7 / Nano Process Industrial Panel PC



## Features

- 17" TFT SXGA (1280x1024) LCD
- NanoBGA2-Base VIA® Eden, C7, Nano Processor
- Anti-Vibration Disk Drive Bay For Hard Disk Drive
- IP-65 Certified Anti-Scratch & Waterproof  
Stainless Steel Front Panel
- Resistive, Capacitive, Infrared Touchscreen (Optional).

## Specifications

System	RS-2917M
Processor (Optional)	NanoBGA2-Base VIA® Eden, C7, Nano processor.
Memory (Optional)	DDR II DIMM Socket x2, total up to 2GB.
LCD/CRT Controller	Intel® CN700
Ethernet	REALTEK® 81105C Gigabit Ethernet, RJ45 x1.
I/O Port	5x serial ports : RS232 (1x Internal, 3x External), RS485/422/232 (1x External) 1x parallel port PS/2 Keyboard x1 , PS/2 Mouse x1 VGA x1, USB2.0 x4 MIC-in / Line-in / Speak-out, RCA x1 (TV cable in)
Storage Disk Drive	Anti-Vibration 2.5" SATA Hard Disk Drive (Optional) 3.5" SATA Hard Disk Drive (Optional) CF Socket for Compact Flash card Slim DVD Multi RW / Blue-ray (Optional) Card Reader x1 with USB2.0 x1 (CF / SD / MS / SM / MMC, on side chassis)
Expansion Slot	Mini PCI x2
OS Support	Windows XP® Embedded, Windows® 7
<b>Mechanical</b>	
Construction	Heavy-duty steel chassis, (or optional stainless steel front panel) IP-65 certified anti-scratch steel front panel
Mounting	Panel mount
Dimension	17.8" (W) x 15.1" (H) x 3.5" (D) / (452mm x 384mm x 88mm)
Net Weight	29.5 lb (13.4 Kg)
<b>Environmental</b>	
Operating Temperature	32°F ~ 122°F(0°C ~ 50°C)
Storage Temperature	-4°F ~ 140°F(-20°C ~ 60°C)
Storage Humidity	10% to 90%@ 35°C, non-condensing
Vibration	Random operation 1.0G, 5~500Hz
Shock	10G peak acceleration (11 msec. Duration)
EMC	CE / FCC Class A
<b>Power Adapter</b>	
AC input	100~240V (50 / 60Hz) 1.8A
DC output	12V, 5A 60W
<b>Optional</b>	
Touchscreen	Resistive, Capacitive, Infrared.
Wireless LAN	802.11a/b/g/n or 802.11 a/b/g

Note : All Specifications are subject to change without notice.