

RS-3219K : 19" KIOSK OEM/ODM



SPECIFICATIONS

Processor	Intel Core™ 2 Duo, Pentium®, Celeron® desktop processor LGA 775 CPU socket, 533/800/1066 FSB
Chipset	Intel 945G / ICH7
Memory	2x DDR2 DIMM, Max. 4GB, 667MHz
Storage	2.5" or 3.5" SATA hard drive (Max. 2TB)
Video	19" (1280 x 1024) SXGA TFT-LCD with CCFL backlight, 16.7M colors Integrated Intel 945G, GMA950 graphic core (share memory 64/128/224MB) VGA port (support ~ 1600x1200 resolution) Support for simultaneous display on LCD and external monitor
Audio	Realtek ALC655 6-channel AC'97 Rev2.3 CODEC Two integrated stereo speakers

	Line out / line in / microphone ports
Interface ports	PS/2 Keyboard PS/2 Mouse RJ45 LAN 2x USB 2.0 2x Serial : 2xRS232 VGA RCA (TV antenna cable in) DC-in SD/MS/MMC/xD 4x USB 2.0 2x IEEE 1394 Line out / line in / microphone
Touch Screen	19", 5 wire resistive touch screen
USB Port	7x USB 2.0 ports
Card Reader	SD/MS/MMC/xD
Expansion Slots	2x Mini PCI slot
Communications	Marvell 88E8053 Gigabit LAN, Wake-on-LAN ready
Fan Speed Control	The fan speed can set by temperature of CPU
Watch Dog	Can be set by 500ms, 1, 2, 4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer
Power Lost Recovery	System will auto power on when AC connected. Don't need to press power button.
Packing	Wooden case + foam
Enclosure	2.0mm SPCC
Power Adapter	Input : AC / 100~240V (50/60Hz) 2.5A Output : DC/20V, 7.5A 150W

Optional	
Color	We can paint your own color
OS	Windows 7 / XP Pro Embedded
Specifications are subject to change without notice.	