

## RS-5622K : 22" KIOSK OEM/ODM



### SPECIFICATIONS

<b>Processor</b>	Intel Core™ 2 Quad, Core™ 2 Duo, Pentium®, Celeron® desktop processor LGA775 CPU socket, 533/800/1066MHz FSB
<b>Chipset</b>	Intel Q965 / ICH8
<b>Memory</b>	2x DDR2 DIMM, Max. 4GB, 800/667MHz
<b>Storage</b>	2.5" or 3.5" SATA hard drive (Max. 2TB)
<b>Video</b>	22" (1680 x 1050) WXGA TFT-LCD with CCFL backlight, 16.7M colors  Integrated Intel Q965, GMA3000 graphic core (share memory up to 384MB)  VGA port (support ~ 1600x1200 resolution)  Support for simultaneous display on LCD and external monitor
<b>Audio</b>	Realtek ALC888 HD Audio

	<p>Two integrated stereo speakers</p> <p>Line out / line in / microphone ports</p>
<b>Interface ports</b>	<p>PS/2 Keyboard</p> <p>PS/2 Mouse</p> <p>RJ45 LAN</p> <p>2x USB 2.0</p> <p>2x Serial : 2xRS232</p> <p>VGA</p> <p>RCA (TV antenna cable in)</p> <p>DC-in</p> <p>SD/MS/MMC/xD</p> <p>4x USB 2.0</p> <p>Line out / line in / microphone</p>
<b>Touch Screen</b>	22", 5 wire resistive touch screen
<b>USB Port</b>	10x USB 2.0 ports
<b>Card Reader</b>	SD/MS/MMC/xD
<b>Expansion Slots</b>	2x Mini PCI slot
<b>Communications</b>	Marvell 88E8053 Gigabit LAN, Wake-on-LAN ready
<b>Fan Speed Control</b>	The fan speed can set by temperature of CPU
<b>Watch Dog</b>	Can be set by 500ms, 1, 2, 4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer
<b>Power Lost Recovery</b>	System will auto power on when AC connected. Don't need to press power button.
<b>Packing</b>	Wooden case + foam
<b>Enclosure</b>	2.0mm SPCC

<b>Power Adapter</b>	Input : AC / 100~240V (50/60Hz) 2.5A Output : DC/20V, 9A 180W
<b>Optional</b>	
<b>Color</b>	We can paint your own color
<b>OS</b>	Windows 7 / XP Pro Embedded
Specifications are subject to change without notice.	