

# RS-6917



# 17" Medical Panel PC/TV

Give everything you want within a monitor

1. IP65 Solution
2. Resistance to 10% Bleach Solution
3. Touch Screen Option
4. Fanless Available

## APPLICATIONS

- Kiosk
- Military
- Banking
- Computer Class
- Thin Client
- Government Building
- Hospital
- Factory Floor

## Wall Mountable

VESA mount compliant mounting holes for healthcare, other industries for efficiency and space saving in the workplace.

*All-In-One  
for Better life*

Web Camera



Bluetooth



Touch Screen



Wireless LAN



TV Tuner Card

## Support

- VIA NANO / C7 / Eden ULV
- DDR II So-DIMM to 4GB
- SATA II 2.5" HDD Support to 500G or above
- Slim CD / DVD / COMBO / DVD Dual

## Optional



# 17" Medical Panel PC/TV

Give everything you want within a monitor

## RS-6917



*All-In-One  
for Better life*



## Specifications

<b>CPU</b>	* Onboard V4 Eden ULV processor 1.6GHz (VIA Nano or C7 Optional)
<b>Chipset</b>	* VIA VX800
<b>Memory</b>	* 2x DDRII So-DIMM memory slots (supports up to 4GB memory) * Supports 1.8V DDRII DIMM * Supports DDRII 667/533/400 DIMM
<b>HDD</b>	* 2.5 size (Up to 500GB or above)
<b>Optical Device</b>	* Slim CDROM / DVDROM /Combo (DVD+CDRW) / DVD RW
<b>Expansion Slots</b>	* 2x mini PCI slot (internal slot) * 1x Compact Flash slot (Internal slot) CF
<b>Audio</b>	* Built-in 2x speakers. (Optional) * Realtek ALC888 6-channel HD Audio.
<b>LAN</b>	* Marvell 88E8053 LAN Controller supporting 10/100/1000 BASE-T.
<b>USB Port</b>	* External 4x USB 2.0 ports (Internal 2x USB 2.0 jumper pin) * Integrated in VIA VX800, VIA Chrome9 HC3 DX9
<b>VGA</b>	Display resolution : 1280x1024 (SXGA). * IGP (share memory up to 64/128/256MB). CRT (support 1920x1440 resolution).
<b>Back Panel I/O Ports</b>	1x PS/2 Keyboard 1x PS/2 Mouse 1x RJ45 (2x RJ45 Optional) 4x USB 2.0 1x Serial 1x VGA 1x Audio I/O (Line In/ Line Out/ MIC) 1x Power connector 1x Button board On/Off
<b>Wireless LAN (Optional)</b>	32bit Mini-PCI card Interface. Support 64 and 128 bit WEP Encryption * 802.11b/g or 802.11n/b/g
<b>Touch Screen (Optional)</b>	Internal RS-232 for Touch Screen Control Board 17", 5 wire resistive touch screen
<b>Watch Dog</b>	Can be set by 500ms, 1, 2, 4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer
<b>Power Lost Recovery</b>	System will auto power on when power failure
<b>Measurements</b>	Wide : 39.2cm ; High : 43.5cm ; Thick : 8.8cm (without the stand)
<b>Weight</b>	8Kg(with all spec) ; 5.4Kg(without stand) ; 5Kg(barebone without stand)
<b>Power Adapter</b>	* IEC 60601-1 Power adaptor 55W * Input : AC / 100~240V (50/60Hz) 2.5A * Output : DC / 19V, 2.89A

\*\*\* Plastic Front side support IP65.



**RISE COMPUTER INC.**

9F, No. 306-3, TaTung Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan

TEL: 886-2-26439992 (Rep) Fax: 886-2-26471298

http://www.rise.com.tw E-mail: sales@rise.com.tw